

# TELIC

## Photomask - Large

### Substrates

- Soda Lime
- Borosilicate (Eagle, D263, AF32, Borofloat)

### Applications

- Flat Panel Displays
- PCB Tooling Masters
- MCM Masks

## SUBSTRATE SPECIFICATIONS

SIZES: Square or Rectangular Shapes up to 50" or 1270mm

THICKNESS: 00.010" - 0.220" (0.30mm - 6mm) non standard thickness is available upon request

SURFACE: All plates are polished on both sides and inspected to be free of glass defects > 5 microns

FLATNESS: <15 microns / 100mm x 100mm

## FILM SPECIFICATIONS

CHROME: Vacuum Deposited, DC Sputtered in Class 100 Environment

THICKNESS/OPTICAL DENSITY: Standard: 1600Å /O.D.=4.0 ± 0.3 @ 530nm. Custom thicknesses up to 5 microns

### REFLECTIVITY:

Low Reflective - LRC	<8% @ 450nm
Mid Reflective - MRC	<33% @ 450nm
High Reflective - HRC	<48% @ 450nm
Blue - R632	<5% @ 632nm
Blue/Chrome/Blue - R632/632	<5% @ 632nm Both Sides
Green - R850	<5% @ 850nm
Green/Chrome/Green - R850/850	<5% @ 850nm Both Sides

### PROCESS:

- Etchable in all conventional Wet Etch systems
- Plasma Grade recommended for Dry Etch systems

### PHOTORESIST:

5300Å AZ 1500 filtered to 0.045 microns at point of use. Fringeless and Regular Spin Available.

Custom Photoresist options include all widely used positive and negative optical and E-beam resist available. Including: AZ MIR701, AZ P4600, AZ 5206, AZ 9260, AZ nLOF 2000, AZ 6615, AZ ECI3027S1800, HR200, IP3500, IP3600, PMMA, AR N7700

LOR A, LOR B, PMGI

24832 Avenue Rockefeller,  
Valencia, CA 91355, USA  
E: [sales@teliccompany.com](mailto:sales@teliccompany.com)

[www.teliccompany.com](http://www.teliccompany.com)

T: 661.702.8603  
TF: 888.TelicCo  
F: 661.257.6802